

SEDAR

— Since 1892 —

RB 16-44 Roller Blind CS **Louvo Cassette Motorized System®** **Technical Summary**



About this Document

This document serves as a concise technical summary for the **RB 16-44 Roller Blind CS Louvo Cassette Motorized System**[®], aimed at designers, specifiers and estimators. It highlights the necessary technical information for project planning. For comprehensive understanding, we offer two additional resources:

1. System Brochure:
 - Features photos and visual representations of the product.
 - Outlines potential use cases.
 - Showcases the aesthetic applications of the system.
2. Technical Document:
 - Contains in-depth technical specifications.
 - Assists engineers, installers, and architects with detailed engineering insights.

To access these documents, click on the links provided below or scan the QR code to be directed to the corresponding resource.



[16-44 Documents](#)



[Roller Blinds Fabric Specifications](#)

General Information

Brand	Sedar
System	16-44 Roller Blind CS Louvo Cassette Motorized Rail

Fabric

Fabric Description	Varies - See Fabric Specification Document
Fabric Color	Varies - See Fabric Specification Document
Fabric Properties	<ul style="list-style-type: none">• Transparency/Openness• Fenestration Data• Fire Resistance Rating• Environmental Requirements Varies - See Fabric Specification Document

System Limitations

Minimum Width	20 cm
Maximum Width	220 cm
Minimum Height	20 cm
Maximum Height	300 cm

Note: Larger dimensions are allowed through Ultrasonic Welding.

System Components

System Brackets	Galvanized steel powder-coated brackets available in silver, with a capacity of 6.5 m ² or 7.5 kg, 1 mm thick.
Tube	Aluminum tube available in 40 mm diameter.
Bottom Rail	<ul style="list-style-type: none">Aluminum powder-coated bottom rail, dimensions 10 mm x 25 mm x 2 mm thick. Colors available are white, and cream.Round shaped one 15 mm dia.
Bottom Rail End Cap	Bottom rail end caps are installed at the edge of the bottom rail for safety and aesthetic purposes, fiber plastic, available in white, gray, and cream.
End Plug	Attached at the opposite side of the tube, serving as a connector between the bracket and the aluminum top rail. Made of fiber plastic, 40 mm for this system.
Louvo Cassette	Aluminum cassette, available in white and cream.
Motor	Somfy Sonesse® 30 RTS featuring Radio Technology Somfy (RTS) for wireless control.

Operation

Operation Type	Remote controlled and automation compatible*
-----------------------	--

Installation

Installation Brackets	Standard or design brackets as previously described, fitted with provided screws.
------------------------------	---

Rolling

Rolling	Standard back rolling.
----------------	------------------------

***Note:** Contact your system integrator for automation system.

Other Relevant Documents

To further explore **the RB 16-44 Roller Blind CS Louvo Cassette Motorized System®**, please click the links below or scan the QR codes. These will direct you to our System Brochure and Technical Document, offering in-depth information and visual guides to assist in your project planning.



[16-44 Documents](#)



[Roller Blinds Fabric Specifications](#)

Projects and Professionals Contact Information

For inquiries about **the RB 16-44 Roller Blind CS Louvo Cassette Motorized System®** or to utilize our Projects Department's bespoke services, please contact us. Our team is ready to assist with product details, installation, and custom solutions, ensuring your design needs are expertly met. Contact us using the QR code below for guidance in transforming your spaces with innovation and style.



Email: projects@sedarglobal.com

Projects Hotline: [+971502313453](tel:+971502313453)